

	Type	L #	Hits	Search Text	DBs
6	BRS	L6	17	handle with flange with (damp\$5 near2 vibration)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT
7	BRS	L7	173	handle same flange same (damp\$5 near2 vibration)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT
8	BRS	L8	163	7 not us.pc.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT
14	BRS	L14	63896	(damp\$5 near2 vibration)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT
37	BRS	L37	68983	15/\$.ccls.	US-PGPUB; USPAT
38	BRS	L38	157	14 and 37	US-PGPUB; USPAT
39	BRS	L39	72	38 and handle	US-PGPUB; USPAT
41	BRS	L41	38376	"56"/\$.ccls.	US-PGPUB; USPAT
42	BRS	L42	85	14 and 41	US-PGPUB; USPAT
44	BRS	L44	15182	"404"/\$.ccls.	US-PGPUB; USPAT
45	BRS	L45	90	14 and 44	US-PGPUB; USPAT
46	BRS	L46	35	45 and handle	US-PGPUB; USPAT